Technical data Engine Brand/Manufacturer YaMZ 238-DK-1 Type V-type with turbocharger Nominal power, h.p (kW) 290 (213) Fuel tank capacity, L 540 Feeder Width, mm 680 Number of rollers, pcs 5 hydraulic Reverse Metal detector **Chopping unit** Diameter/width, mm 750/650 Number of knives, pcs 24 (V-type positioning) 838 Rotational speed, RPM Cutting length, mm 3.5/8/20 Cutting length selection by switching from cabin Corn cracker removable, rotary Type Rotor number of rotations, RPM 3,848 Discharger Rotor accelerator diameter, mm 510 Rotor rotational speed, RPM 1,678 Silage duct line turning angle, deg. 180 Chassis Transmission hydrostatic Transporting speed, km/h up to 20

² Adviser

up to 10

340

8,600/3,880/3,940

9,400±280

4.5 (6 rows)

5.0

3.0

information system with LCD-display, situational framing

and voice notification.

Operating speed, km/h

Comfort Cab¹ complete set

Overall dimensions (without header)

Mass (basic version, without fuel), kg

Harvesting of rough-stem cultures, m

option

without prior notice to the market.

Length/width/height (in transporting position), mm

leaf-spring equipped, pressurized, double-seat cabin with

audio system, reinforced noise insulation, equipped with

air conditioner, heater and cooling box.

ROSTSELMASH reserves the right to improve individual machine characteristics

Clearance, mm

Adviser² system

Headers (width)

Grass harvesting, m

Swath pickup, m

standard,

¹ Comfort Cab

Cabin